

| ENGINE | NARROW | WIDE |
|---------------------------------------------------|-----------------------------------------------------------------|-------------------|
| Engine Type | Water-Cooled, 4 Cycle Diesel Engine with 3 Cylinder, EPA Tier 4 | |
| Model Name | KUBOTA D1703-M | |
| Total Displacement | 100.5 cu.in. (1.647 L) | |
| Engine Power SAE J1995 Gross | 24.8 HP (18.5 Kw/rpm) | |
| Max. Torque | 97.4Nm (71.8lb-ft) @ 1,500 rpm | |
| Rated Speed | 2,200 rpm | |
| Low Idling Speed | 1,100 rpm | |
| DIMENSIONS | | |
| Overall Length-Transport | 114.1" (2,897 mm) | 114.6" (2,911 mm) |
| Overall Length (W/O Bucket) | 87.9" (2,233 mm) | 87.3" (2,218 mm) |
| Overall Height | 65.4" (1,660 mm) | 63.9" (1,623 mm) |
| Overall Width (W/O Bucket) | 36" (914 mm) | 42" (1,067 mm) |
| Wheelbase | 42.4" (1,078 mm) | 42.6" (1,082 mm) |
| Hinge Pin Height at Max. Lift | 84.8" (2,150 mm) | 82.3" (2,090 mm) |
| Reach at Max. Lift and 45° Dump | 63.6" (1,615 mm) | 57.8" (1,467) |
| Track Width STD. | 7.8" (200 mm) | 9.1" (230 mm) |
| Ground Clearance (in the center) | 11" (279 mm) | |
| Ground Clearance (on the side) | 3.7" (93 mm) | |
| Angle of Departure | 31° | |
| Operating Weight (W/O Operator) | 3,638 lbs (1,650 kg) | |
| Rated Operating Capacity (35%) | 1,200 lbs (544 kg) | |
| Tipping Load | 3,429 lbs (1,555 kg) | |
| PERFORMANCE | | |
| Attachment Mounting System | CII (Common Industry Interface) | |
| Travel Speed (Fwd/Rev) | 4.94 mph (7.96 km/h) | |
| Battery Capacity | 12V, 60AH | |
| Main Auxiliary Hydraulic Flow (High Flow) | 12.68 gal/min (48 L/min) | |
| Main Auxiliary Hydraulic Pressure (High Flow) | 2,755 psi (19 MPa) | |
| Secondary Auxiliary Hydraulic Flow (Low Flow) | 2.6 gal/min (9.9 L/min) | |
| Secondary Auxiliary Hydraulic Pressure (Low flow) | 3,045 psi (21 MPa) | |
| Driving System Operating Pressure | 5,801 psi (40 MPa) | |
| SERVICE AND FILL CAPACITIES | | |
| Fuel Tank Capacity | 8.45 gal (32 L) | |
| Hydraulic System | 8.45 gal (32 L) | |